

DEFINING CYBER SECURITY FOR SMALL NETWORKS

PRODUCT HIGHLIGHT

UNIQUE GATEWAY ARCHITECTURE

Combine digital security with productivity and improve your network's protection level. Its Policy based ISP Failover & Load Balancing to distribute important applications over more robust Internet links and less imp. App. over backup connections and also to provide redundancy.

SIMPLICITY, SECURITY & SCALABILITY

The Next-Generation Firewall allows for the creation of policies for applications, users, groups, programming, and other features that are not available in conventional firewalls.

COMPLETE VISIBILITY (BYOD)


UTM enabled HotSPOT Gateway Management engine feature enhance the in NG-Series to inspect, detect and monitor the traffic and control the devices being used by employees or guest.

MODERNITY & FLEXIBILITY

Secure Access Gateway is the core engine of NG-Smart VPN technology. It is ideal for establishing a secure tunnel over any WAN link. Result- reductions in cost, optimization of time and easy management, alternative to costly MPLS.

3G |4G EXTENSION

NG15 includes built-in 4G Modem* that allows additional WAN connectivity or a redundant link for maximum reliability.



These entry-level firewall are the ideal choice for budget-conscious Small Businesses, Enterprise Branch Office, Retail and Small or Home offices to manage fast & secure their entire network through a single window. The All-In One appliance has been designed & engineered to combinedly serve the functionalities.

In addition to UTM features, equipped with Hotspot Gateway functionalities for total user management for both wired and wireless network. 100% uptime is achieved by 4G LTE Cellular WAN connectivity. The Intel Quad -core technology makes them highly efficient and as they're Fan-less, they won't add unwanted noise and can be placed in office without any much special arrangement.

It designed with feature to provide seamless failover between MPLS over Smart VPN on xDSL / 4G LTE Cellular WAN without modifying the existing network.

FEATURES	HARDWARE SPECIFICATIONS
Interfaces	04 GbE
Internal 4G LTE SIM Module	Optional *
Firewall Throughput	3.0 Gbps
Firewall IMIX	850 Mbps
Concurrent Sessions	3,250,000
New Sessions / Sec.	20,000
VPN Throughput	250 Mbps
NGFW Throughput	390 Mbps
AV Throughput	400 Mbps
IPS Throughput	580 Mbps
Storage-SSD	16-32GB
Memory / Max	2 / 4 GB
Firewall Policies	Unrestricted
Maximum Connections	Unrestricted
Inbound NAT Connection	Unrestricted
Local User Database	Unlimited
Suggested concurrent Users /Devices	20-25

SPECIFICATIONS

NETWORK Services

- Multi-Link Auto Failover.
- 4G LTE Support : SIM* | USB Dongle | Tethering
- Operating modes: NAT/route, transparent (bridge), and mixed mode
- Configurable LAN/WAN/DMZ Ports
- NAT & ALG Support - DNAT ,SNAT , PAT
- Routing - Static, Source , Destination & Policy based
- Policy Rule : predefined, custom & Grouping
- Authentication, Authorization & Accounting.
- Support Multicast Forwarding , VLAN Tagging
- Static, DHCP, PAP/CHAP Support

NETWORK SECURITY

- Stateful & Deep Packet Inspection Firewall
- Application Visibility & Control.
- Demilitarized Zone (DMZ)
- Zone - based access control list.
- Access scheduling
- Flooding detection and protection
- Stops all types of DoS; Prevents DNS Spoofing & Flooding, Bypass Websites, Packet Capturing
- IP-Mac bind, MAC Whitelist / Blacklist.
- Comprehensive DNS policy

LINK LOAD BALANCING

- Bi-directional link load balancing
- Outbound link load balancing includes policy based routing and weighted, and dynamic detection
- Inbound link load balancing supports Smart DNS & dynamic detection
- Automatic link switching based on Traffic, latency, jitter, connectivity etc.
- Link health inspection with ARP, PING, and DNS

URL FILTERING

- Web or URL / IP / Geography / Keyword / Port / Application Filter
- Block predefined categories on specific time
- Create | Edit | Delete Manual Categories & Add exception
- Manually defined web filtering based on URL, web content. Key word and MIME header
- Web filtering profile override: allows admin to temporarily assign different profiles to User/IP
- Web filter local categories and category rating override
- Additional web filtering features:
 - Force Google Safe search
 - Force educational YouTube
 - Exempt scanning encrypted connections on certain categories for privacy

USER| GUEST MANAGEMENT |AAA

- ID & Password login – fixed users
- Approval-based Login.
- Social Media & OTP based login
- BYOD Self & Voucher Registration with OTP
- Create users with auto-expiry, Renew & Block
- Seamless connectivity from Wired to W-LAN
- Auto Login /No Authentication after First Login
- Auto login based on IP & MAC or combination
- Concurrent logins, auto MAC binding
- Easy migration - import/export data
- Restrictions based on Device & OS
- Create user groups & apply policies
- Allow login only when user comes from specific segments

BANDWIDTH MANAGEMENT | QoS

- Define enhanced quality of service (QoS)
- Max/Guaranteed bandwidth tunnels or IP/User basis
- Bandwidth allocated by time, priority, or equal bandwidth sharing
- Restrict users based on data, b/w & time
- Individual and shared bandwidth quota
- Contention ratio based bandwidth allocation.
- Schedule based committed & burstable b/w.
- Configure multiple b/w policy on a user at different hours of day

VIRTUAL PRIVATE NETWORK

- Virtual private network
- SSL VPN - TCP/UDP tunnelling with failover
- Encryption – 3DES,DES,AES, Blowfish
- Hash algorithms - MD5, SHA-1, SHA-2
- Authentication – pre-shared key, certificates
- Supports IKEv1 and IKEv2.
- DH groups - 1, 2, 5, 14, 15, 16, 17...
- NAT traversal & PFS support
- SSL authentication – AD, LDAP, radius, local
- Multi-layer client authentication - certificate, username/password, mac address , OTP*
- Network access - Split and Full tunnelling
- Granular access control to all network resources
- Administrative controls - session timeout, DPD
- User and group policy enforcement
- Multicast support over SSL VPN
- SSL VPN deployment modes: Client to site , Site to Site
- View and manage IPSEC and SSL VPN connections
- Supports SSL VPN clients that run Windows, Linux, iOS & Android

CAPTIVE PORTAL CAPABILITIES

- Intuitive self-service portals for users.
- Customise captive form input fields
- Mobile/desktop responsive login page
- Social media based login, mac based auto login
- Create hourly and day based plans with FUP
- Accounting based on hours, days, data transfer

INTRUSION PREVENTION

- Protocol anomaly detection, rate-based detection, custom signatures, manual, automatic push or pull signature updates, integrated threat encyclopaedia
- IPS Actions: default, monitor, block, reset (attackers IP or victim IP, incoming interface) with expiry time
- IDS sniffer mode
- Predefined prevention configuration

ANTI-VIRUS & ADVANCE THREAT PROTECTION

- Virus, Worms, Trojan detection & removal
- Spyware, Malware, Phishing, Bot & Pharming protection
- Manual, automatic push or pull signature updates
- Scans HTTP/S, FTP, SMTP/S, POP3, IMAP
- Block files based on their type.
- Threat logs with action.
- Compressed file virus scanning
- Spam filtering

ATTACK DEFENCE

- Abnormal protocol attack defence
- Anti DoS / DDoS, including SYN Flood, UDP Flood, DNS Query Flood defence, TCP fragment, ICMP fragment etc.
- ARP attack defence

DATA LEAKAGE PREVENTION

- Restricts file upload over HTTP, FTP, P2P and other file sharing applications.
- Blocks file transfer (upload & Download) over IM like Facebook, Whats-app & other Social Sites
- Controls file upload /download over HTTPS/SSL websites.
- Logging & Reporting in accordance to HIPAA, CIPA compliance.

SYSTEM MANAGEMENT

- System Configuration Backup / Restore
- Auto/ Manual backup of User & Threat Logs
- Enable appliance & PMS remote access
- Set auto/manual firmware updates
- Create Child Admins and check logs
- Set NTP , SMTP Email
- Integrate Syslog, SNMP, Net-flow
- Three levels of users: Admin | Operator | Monitor
- Dynamic real-time dashboard status and drill-in monitoring widgets

LOGS | REPORTING | MONITORING

- Real-time traffic statistic and analytics
- User Management & Account Expiry Report
- Bandwidth ,Data usages & Session Report
- Web Browsing & Records surfing logs of each user
- Search logs based on User, IP, Site ,Time & File Type
- Change Log Report / Activity Timeline
- Comprehensive event logs: system & admin activity audits, routing & networking, VPN, user authentications,
- User & System based overall and user wise analytics
- Real Time monitoring Tools to get visibility into network Traffic & Bandwidth consumption
- On-Appliance (Local) Logging and reporting facilities
- Reports can be exported in PDF, Word and via Email
- System information such as concurrent session, CPU, Memory and temperature
- Support traffic information collection and forwarding via Net-flow

ALERT MANAGEMENT

- Real-time alerts to user on data consumption limit, voucher expiry etc.
- Real-time alerts to admin on link failure & Speed, Remote Access etc.
- Schedule Alerts for specific reports

SMS GATEWAY

- Pre-configured SMS gateway*
- Click –n-configure custom gateway
- Facilitates different message templates

VULNERABILITY ASSESSMENT

- Scans LAN Devices for vulnerability
- Generates summary and detailed reports of found possible threats

CUSTOM DEVELOPMENT

- Personalized development on request*
- Third party application Integration*

HIGH AVAILABILITY

- Active-Passive with state synchronizations
- Stateful Failover to Keep-Alive Sessions
- Redundant heartbeat interfaces

HARDWARE

- Form factor- Desktop
- Memory - 2GB
- SSD – 16~ 32 GB
- Gbps Ethernet Ports - 4.
- 2 USB Ports, 1 VGA, 1HDMI
- Dimension-(mm)-(HxWxD)- 33x135x125

POWER AND RELIABILITY

- 12V/ 2.5 A Power Supply / Adapter
- Operating Temperature - (0°C ~ 40°C)
- Storage Temperature - (-20°C ~+70°C)
- Relative humidity - 10% - 90%, no condensing

OTHER ADD-ON OPTIONS*

- 4G LTE SIM module
- Wi-Fi Module



All specification and photos are subject to change without prior notice

1. Maximum throughput performance is measured under ideal test conditions using industry standard performance test tools. 2. Firewall UDP throughput performance is based on RFC 2544 guidelines. 3. All Performance values are upto or rough guideline only and vary depending on system configuration. 3. IPS throughput (http) measured using default IPS rule set and 512KB object size. 4. VPN throughput measured using multiple tunnels with 512KB response size. 5. Testing done with multiple flows through multiple port pairs. *if all slot populated

www.netxgate.com | 9891@netxgate.com | +91-9891-412158

#628 ,Signature Global Mall , Sec-3 , Vaishali ,
GZB Delhi /NCR – 201012 (INDIA)

6/1 , 1st Main , Vasanth Nagar
Bangalore – 560 052 (INDIA)